

# 910 COAXIAL CABLES

---

COAXIAL 6,8 MM, 17 DB/100M 800 MHZ, 100M



Code : **9100063**

Model : **CE-150**

#### Description

Coaxial cable with physically expanded dielectric and copper insulation. Flame-retardant. Conforms to norm EN 50117.

#### Applications

Used to transmit the TV signal on the terrestrial band or on the IF satellite band.

#### Characteristics

Supplied in coils of 100 m and packed in a carton box.

CÓDIGO-CODE-CODE		9100064		9100063	
MODELO-MODEL-MODÈLE			CE-140	CE-150	
Conductor interno Internal conductor Conducteur interne	Mat		CU		
	mmø		1.13		
Dieléctrico Dielectric Dielectrique	Mat		PEE físico/phisical/physique		
	mmø		4.80		
Blindaje Shielding Blindage	Mat		CU/PET+BOPP		
Malla Mesh Tresse	Mat		CU		
Cubierta Cover Gaine	Mat		PE negro/black/noir	PVC blanco/white/blanc	
	mmø		6.80		
Atenuación/100m Attenuation / 100m Atténuation/100m	dB	50 MHz	3.3		
		470 MHz	12.9		
		862 MHz	17.8		
		2150 MHz	29.6		
Pérdidas de retorno Return loss Pertes de retour	dB	5-470 MHz	>26		
		470-2150 MHz	>24		
Resistencia a corriente contin. Resistance to DC current Resistance au courant continu	Ω/Km		34		
Radio mínimo de curvatura Minimun bending radius Rayon minimun de courbure	mm		35		
Impedancia característica Characteristic impedance Impédance caractéristique	Ω		75 ±3		
Unidades embalaje Units per packing Unités par emballage			100		
Peso Packing weight Poids emballage	Kg		4.57		
Dimensiones embalaje Packing dimensions Dimensions emballage	mm		310 x 310 x 90		

CU - Cobre  
AL - Aluminio

PL - Poliéster  
PEE - Polietileno expandido

PVC - Policloruro de vinilo  
PE - Polietileno

CCA -Aluminio cobreado  
CCS -Acero cobreado

BOPP - Polipropileno biorientado  
PET - Tereftalato de polietileno

CÓDIGO CODE CODE	MODELO MODEL MODÈLE	CLASE DE APANTALLAMIENTO SHIELDING CLASS BLINDAGE CLASSE	EUROCLASE REACTION TO FIRE CPR EUROCLASSE
9100021	CE-753	A	Eca
9100056	CE-743		
9100058	CE-754	B	
9100068	CE-763	A	Dca s1,d0,a1
9100074	CE-764		
9100064	CE-140		Fca
9100063	CE-150		
9100060	CE-860		Eca
9100057	CL-201		