912 TV-SAT AND MODULATOR EQUIPMENT

DIGITAL MODULATOR 2XAV DVB-T



Code : **9120194**

Model : **DM-102**

Description

Digital modulator designed to generate a digital terrestrial TV channel in DVB-T from one or two audio/video signals. Programmable using PC software and a wireless programmer.

Applications

Collective digital terrestrial TV installations where it is necessary to generate an entire DVB-T channel which contains one or two services generated locally from SAT receivers, DVD or videosurveillance cameras. Compatible with all collective TV installations since the channels are distributed throughout the terrestrial band: BI, BIII, BS and UHF.

Characteristics

Outstanding quality of the generated output channel. Audio/Video signal inputs via 3.5 mm mini-jack connectors. Zamak chassis with metal side covers. F-type connectors. Supplied with diplexing and multiplexing bridges.

CODE			9120194	
MODEL			DM-102	
A/V input				
Number of inputs			2	
Input connector			A/V minijack	
Video input signal			CVBS	
Video input standard			PAL/SECAM/NTSC	
Video input level	Vpp		MPEG-2/H.262 (ISO/IEC-13818-2 MP@ML)	
Resolution			PAL/SECAM: 720x576 @25fps NTSC: 720x480 @30fps	
Audio input level	Vpp		0,3 - 1	
Audio codification	dB		MPEG-1/Layer 2 (ISO/IEC-11172-3)	
COFDM modulator				
TV system			DVB-T / DVB-H DVB: EN 300744	
Output offset	MHz		-1/6, -1/8, 0, +1/8, +1/6 DVB-T	
Mode			2K, 8K, 4K (DVB-H) DVB: EN 300744	
Modulation			QPSK, 16QAM, 64QAM DVB: EN 300744	
F.E.C.			1/2, 2/3, 3/4, 5/6, 7/8 DVB: EN 300744	
Guard interval			1/4, 1/8, 1/16, 1/32 DVB: EN 300744	
MER	dB		39 ±2,0	
Output RF				
Output connector			F female	
Frequency range	MHz		47-862	
Frequency step	MHz		0,25	
Output level	dBµV		80 ±2,0	
Output level adjust	dB		20	
Bandwidth	MHz		8, 7, 6, 5 DVB-H	
Through loss in the mixture	dB		0,9 ±0,1	
General features				
Power supply	V 	+3,3	+5,2	+12
	mA	1050	835	50
Operarting T close equipment			-10+65	
Room T with / without fan			-10+55/+45	
Protection index			IP30	
Units per packing			1	
Packing weight	Kg		1.22	
Packing dimensions	mm		270 x 170 x 38	