

# 912 TV-SAT AND MODULATOR EQUIPMENT

## AV MODULATOR STANDARD M/N, WIDEBAND



Code : **9120240**

Model : **MS-565**

### Description

Mono audio modulator in VSB vestigial side band, designed to work with adjacent channels. The audio input can be mono or stereo, in which case the channel will be modulated with a mono audio containing the two stereo channels. The modulator MS-569 covers the B/G, D/K and I standards. The modulator MS-565 covers the M-N standard.

### Applications

MATV installations where it is necessary to generate an analogue TV channel with mono sound from the audio and video signal from equipment with mono or stereo sound.

### Characteristics

Essential features of this equipment are the high carrier to noise ratio together with a very reduced spurious level in the band. Modulation in VSB vestigial side band filtered by means of a SAW surface acoustic wave filter, in any TV channel, including the interbands. F type connector and miniDIN connector for audio/video. Supplied with the multiplexing bridge.

CODE	9120239				9120240	
MODEL		MS-569			MS-565	
TV System		AM-TV B/G CCIR	AM-TV I UK	AM-TV D/K OIRT	AM-TV M - N	
Frequency range	MHz	46-862	46-862	46-862	46-862	
Frequency step	KHz	250				
Output channel		2 - 4 5 - 12 21 - 69 S1 - S41	2 - 4 5 - 12 21 - 69 S1 - S41	R1 - R4 R5 - R12 21 - 69 S1 - S41	2 .. 6 A5 .. A1 A .. I 7 .. 13	J .. W AA .. ZZ 14 .. 83
Video input level	Vpp	0.7-1.4 (75 )				
Audio input level	Vpp	0.2-2.0 (>20 )				
Audio		Unbalanced				
Output level	dB $\mu$ V $\pm$ TOL	84 $\pm$ 2,0				
Output level adjust	dB	15				
Output level stability	dB	0.5				
Multiplexing through loss	dB $\pm$ TOL	0.9 $\pm$ 0,1				
Carrier/noise ratio (C/N)	dB	60				
Audio signal/noise ratio	dB	>50				
Return loss	dB	>15				
Chroma-luminance delay	ns	<40				
Non-linearity of luminance	%	<2				
Differential gain	%	<3				
Differential phase		<3				
Response to the 2T pulse	%	<3				
Connectors		F female				
Audio/video connector		miniDIN (8 pin)				
Power supply	V $\cdots$	+3.3	+5.2	+12		
	mA	325	190	120		
Operating temperature	°C	-10..+65				
Protection index		IP 20C				
Units per packing		1				
Packing weight	Kg	1.4				
Packing dimensions	mm	265 x 165 x 40				