

913

MULTISWITCHES

17X24 CASCADABLE MULTISWITCH

Code : **9130138**

Model : **ML-406**

Description

Cascadable multiswitches for 16 polarities and terrestrial TV with 20, 24 and 32 outputs. The outputs are amplified in the satellite IF band. In the terrestrial band they can be configured to function in either active or passive mode. Need to be powered from each individual receiver so that the switching and amplification of each derived output will function.

Applications

Medium-sized collective satellite and terrestrial TV installations. It is essential that they be mounted along with end multiswitches, so as to obtain distributions of up to 128 outlets on a single line if they are installed with intermediary amplifiers.

Characteristics

Shielded metal chassis with plastic supports. F-type connectors. Earth.

CODE	9130137				9130138		9130175	
MODEL		ML-405		ML-406		ML-408		
TV system		FM-TV / DVB-S / AM-TV / DVB-T						
Connection		F female						
Inputs/outputs		17/17						
Tap outputs		20		24		32		
Frequency range	MHz	47-862	950-2150	47-862	950-2150	47-862	950-2150	
PASSIVE MODE								
Tap loss	dB±TOL	26 ±2.0	2 ±2.0	26 ±2.0	2 ±2.0	28 ±2.0	5 ±2.0	
Output level	dBµV	-	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	-	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	-	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	
ACTIVE MODE								
Tap loss	dB±TOL	6 ±2.0	2 ±2.0	6 ±2.0	2 ±2.0	8 ±2.0	5 ±2.0	
Output level	dBµV	95 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	95 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	95 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	
ACTIVE / PASSIVE MODE								
Tap equalization	dB	1	2	1	2	1	2	
Rejection between bands	dB	> 25 TV/SAT > 65 SAT/TV						
Isolation between users	dB	> 25 TV > 30 SAT						
Isolation of switching	dB	> 30 SAT/SAT						
Switching the outputs		DiSEqC 2.0 14V $\overline{\text{---}}$ /18V $\overline{\text{---}}$ 0/22 kHz						
Power supply of the LNB		2050 mA /13 V $\overline{\text{---}}$						
Output voltage	V $\overline{\text{---}}$	13 V $\overline{\text{---}}$						
Consumption from the receiver	mA	42 ±2.0 (14/18V $\overline{\text{---}}$)						
Operating temperature close to equipment	°C	-10..+65						
Room temperature with/without fan	°C	-10..+55/+45						
Protection index		IP 30						
Units per packing		1	5	1	5	1	5	
Packing weight	Kg	1.51	8.05	1.65	8.75	1.57	7.9	
Packing dimensions	mm	395 x 245 x 55	400 x 290 x 270	395 x 245 x 55	400 x 295 x 270	333 x 315 x 44	335 x 335 x 460	