913 MULTISWITCHES

5X16 FINAL MULTISWITCH, UK PSU

Code : **9130146**

Model : **MB-104**

Description
Final multiswitches for 4 polarities and terrestrial TV with 8, 12 and 16 outputs. The outputs are amplified in the satellite IF band. In the terrestrial band they can be configured to function in either active or passive mode. Need to be powered from each individual receiver so that the switching and the amplification of each derived output will function correctly. The external power supply units provide the required voltage to the LNBs for them to function properly.

Applications
Medium-sized collective satellite and terrestrial TV installations. Installed individually, they can distribute to as many as 16 TV outlets. When combined with cascadable multiswitches, with intermediary amplifiers in place, it is possible to distribute to 64 outlets on a single line.

Characteristics
Shielded metal chassis with plastic supports. F-type connectors. Power supply connector is a 9.5 x 2.1 mm jack to feed the LNBs.

CODE		9130144		9130145		9130146	
MODEL		MB-102		MB-103		MB-104	
TV system		FM-TV / DVB-S / AM-TV / DVB-T					
Connection		F female					
Inputs		5					
Tap outputs		8		12		16	
Frequency range	MHz	47-862	950-2150	47-862	950-2150	47-862	950-2150
PASSIVE MODE							
Tap loss	dB±TOL	19 ±3.0	-2.5 ±4.0	20 ±3.0	-1 ±4.0	20 ±3.0	-1 ±4.0
Output level	dBµV	-	100 (IMD_3 -35 dB) 95 (IMD_2 -35 dB)	-	100 (IMD_3 -35 dB) 92 (IMD_2 -35 dB)	-	100 (IMD_3 -35 dB) 92 (IMD_2 -35 dB)
ACTIVE MODE							
Tap loss	dB±TOL	-1 ±3.0	2.5 ±4.0	0.0 ±3.0	-1 ±4.0	0.0 ±3.0	-1 ±4.0
Output level	dBµV	99 (DIN 45004B)	100 (IMD_3 -35 dB) 95 (IMD_2 -35 dB)	96 (DIN 45004B)	100 (IMD_3 -35 dB) 92 (IMD_2 -35 dB)	96 (DIN 45004B)	100 (IMD_3 -35 dB) 92 (IMD_2 -35 dB)
ACTIVE / PASSIVE MODE							
Tap equalization	dB	4	4	4	4	4	2
Rejection between bands	dB	> 20 TV/SAT > 65 SAT/TV					
Isolation between users	dB	> 20 TV > 20 SAT					
Isolation of switching	dB	> 30 TV/SAT					
Switching the outputs		DiSEqC 2.0 14V⎓ /18V⎓ 0/22 kHz					
Power supply of the LNB		1050 mA /13 V⎓					
Output voltage	V⎓	13 V⎓					
Consumption from the receiver	mA	42 ±2.0 (14/18V⎓)					
Operating temperature close to equipement	ºC	-10..+65					
Room temperature with/ without fan	ºC	-10..+55/+45					
Protection index		IP 30					
Units per packing		1	5	1	5	1	5
Packing weight	Kg	0.30	2.00	0.42	2.60	0.55	3.25
Packing dimensions	mm	205 x 105 x 45	225 x 115 x 250	260 x 245 x 55	290 x 270 x 270	260 x 245 x 55	290 x 270 x 270