

904 BROADBAND AMPLIFIERS

EVEREST SAT-UHF-BIII-BI/FM LTE700



Code : **9040143**

Model : **CA-671**

Description

Broadband amplifier for head-end, with four inputs and different frequency configurations, compatible with the transmission of LTE700 and LTE800 mobile telephone signals. Satellite amplifier for one polarity. Separate power supply. UHF Band preamplifiers can be fed means of a switch. Output test-point to adjust the installation without having to disconnect the TV signal.

Applications

Large-scale digital and analogue SMATV installations which are affected by the transmission of LTE700 and LTE800 mobile telephone signals. Suitable for installations where the channels of each band are received at similar levels. Adjustment by means of switches and regulators which control the gain at each input. Satellite polarity selection by means of switches that select voltage and 22 kHz tone.

Characteristics

Made from zamak and galvanised steel plate to provide maximum shielding. Input and output connectors in the opposite sides to facilitate installation. F-type connectors.

CÓDIGO-CODE-CODE		9040143		
MODELO-MODEL-MODELE		CA-671		
Número de entradas/salidas/test Number of inputs/outputs/test Nombre d'entrées/sorties/test			4 / 1 / 1	
Rango de frecuencia Frequency range Gamme de fréquences	Band MHz	SAT 950 - 2150	UHF 470 - 694	BIII/DAB 160-260
Filtro LTE LTE Filter Filtre LTE			LTE700	
Ganancia Gain Gain	dB _{± TOL}	43 ± 1,0	45/30 ± 1,0 Switchable	30 ± 1,0
Regulación de ganancia Gain adjustment Réglage de gain	dB	20	16	20
Margen de ecualización Adjustable equalization range Plage de réglage de pente	dB	0/8 Switchable		
Nivel de salida Output level Niveau de sortie	dB _{μV}	118,5 (IMD ₃ -35 dB) 112,0 (IMD ₂ -35 dB)	117 DIN 45004B 114 (IMD ₃ -60 dB) 107 (IMD ₂ -60 dB)	
Figura de ruido Noise figure Facteur de bruit	dB	7 ±1,0	8 ±1,0	7 ±1,0
Tensión de salida Output voltage Tension de sortie	Vdc mA kHz	0 / 13 / 18 350 0 / 22	24 60	
Índice de protección Protection index Indice de protection	Vdc mA		24 700	
Temperatura de funcionamiento Operating temperature Température de fonctionnement	°C		-10 ... +65	
Índice de protección Protection index Indice de protection			IP 50D	

