# 941 SENSORS AND ACTUATORS

## NURSE CALL BUTTON (DIN8 CONNECTOR)




Code : **9410313**

Model : **LLC-710**

Description
Handset with a male DIN-8 connector for the LLC-80x and LLC-90x wall peripherals. It has a red nurse call button with Braille, a red LED and a yellow LED that indicates the state of the connection. This pear-type accesory enables patients to place calls, while the red LED reflects the status of the call. Bus peripheral with DIN8 connector. Easy cleaning and connection.

| Code | 9410313 | 9410314 | 9415049 |
|---|---|---|---|
| **Model** | **LLC-710** | **LLC-711** | **LLC-712** |
| BOTONES<br>BUTTONS<br>BOUTONS | LLC-710/711/712: Llamada de enfermera/ Nurse call/ Bouton d'appel<br>LLC-711/712: Control de luces / lights control / commande de 2 éclairages*<br>LLC-712: Control de persiana / Blind control / commande des volets roulants* | | |
| LUCES<br>LIGHTS<br>LUMIÈRES | 3 | | |
| ALIMENTACION<br>POWER SUPPLY<br>ALIMENTATION | 24Vdc | | |
| CONSUMO<br>CONSUMPTION<br>CONSOMMATION | 2 – 6mA | | |
| TENSION CONTROL DE LUCES<br>LIGHT CONTROL POWER SUPPLY<br>CONSOMMATION | 24Vdc | | |
| LONGITUD DEL CABLE<br>CABLE LENTH<br>LONGUEUR DU CORDON | 2 m | | |
| TEMPERATURA OPERACIONAL<br>OPERATING TEMPERATURE<br>TEMPERATURE DE FONCTIONNEMENT | -10°C to 55°C | | |
| INDICE DE PROTECCION<br>PROTECTION INDEX<br>INDICE DE PROTECTION | IP40 | | |
| DIM. | 120 x 60 x 25mm | | |
| PESO<br>WEIGHT<br>POIDS | 20gr | | |
| CONECTOR<br>CONNECTOR<br>CONNECTEUR | DIN8 (Macho/Male/Mâle) | | |

***Modèle livré avec le module de gestion des relais de commandes éclairage et VR.**