972 VIDEO DOOR ENTRY SYSTEM KITS

ENARA KIT 1 BUTTON IBLACK



Code : **9720164**

Model : **KVS-50921**

Description
ALCAD video door entry system kits Include all the necessary material to carry out the installation, with the exception of the cable. Include entrance panel for the building with video camera, power supply and indoor monitor. The installation can be completed with accessories, such as rainshields or decorative frames, and with different extensions, such as second entrance panel or monitors and additional telephones.

ENARA monitor
This kit includes the ENARA monitor, which is the most compact monitor on the market. The compact size makes Enara the perfect monitor for replacements where space is limited. Its new neutral and minimalist design combines perfectly with any kind of decoration in your home, from the most classic to the most avant-garde.
The modern capacitive technology used for the touch buttons ensures a reliable and long-lasting operation, and as there are no electrical contacts or moving parts, the accumulation of dirt that affects the operation of traditional push-buttons is avoided.
The Enara monitor has a very useful function so that nobody interrupts your rest time: the "Don't disturb" function. Its large 4-inch flat screen allows you to identify the person making the call with total clarity and security and also, the on-screen menu allows you to adjust the image to achieve optimal performance in any lighting situation.

CODE		9720164
MODEL		**KVS-50921**
SYSTEM		2-wire
ENARA MONITOR		9630075 MVC-140
• Screen		TFT Color 4"
• On screen menu		Yes
• Communication		Hands Free
• Call volume set		“Don’t disturb”; “low”; “high”
• Pushbuttons		4 touch pushbuttons
• Pushbutton for auxiliary functions		1 touch pushbutton
• Image memory		NO
• Magnetic loop		NO
• Power supply	Vdc	Through the bus (12 ... 18Vdc)
• Consum	mA	25 mA (at rest); 360 mA (working)
• Working temperature	°C	+5... +55 °C
• Connections		Pluggable terminals
• Tap-off and line termination load		Yes, Configurable by means of microswitches
• Mounting		Surface
• Dimensions		120 x 168 x 22
ENTRANCE PANEL		
• Look		iBLACK
• Pushbuttons		1
• Dimensions	mm	128 x 147
• Materials		Aluminum and Polycarbonate
• IP rate protection		IP54
• Camera		CCD Color 1/3"''
• Night vision		White LEDs
• View angle	°	60° (H); 45° (V)
• Adjustable camera	°	10° in any direction
• Working temperature	°C	-10°C ... +55°C
FLUSH BOX FOR ENTRANCE PANEL		9740005 CMO-002
• Dimensions		144 x 131 x 45
• Material		PVC
POWER SUPPLY		9650004 ALS-020
• Primary		230Vac; 50/60 Hz; 0,45A
• Secondary		18Vdc; 2A
• Protected against short circuits		Yes, With LED indicator
• Format		DIN rail 6 elements
• Mounting		DIN Rail or Wall
• Dimensions	mm	105 x 90 x 60
• Working temperature	°C	-10°C ... +65°C
ELECTRIC LOCK (Not included)		
• Suggested		9730062 ABR-015
• Working Voltage	Vdc	12 - 18 Vdc
• Maximum consumption	mA	500 mA
Packing weight	Kg	1,86 Kg
Packing dimensions	mm	300 x 140 x 270 mm