918 MEASUREMENT EQUIPMENT

FIBER OPTIC FUSION SPLICING KIT



Code : **9180013**

Model : **OEQ-102**

Optical fibre fusion kit consisting of an optical fusion splicer with a spare battery and spare electrodes, a precision optical fibre stripper, a stripper and a carrying case.

The fusion splicer is compatible with single core fiber cables of different diameters, from 0.25 mm to 3.04 mm. The two included batteries, which can be easily swapped, allow for up to 400 cycles of splicing and heating in just one charge. The splicer includes a tiltable 4.3" LCD touchscreen.

CÓDIGO		9180013
MODELO		OEQ-102
Fibra compatible Compatible fiber Fibre compatible		mononúcleo / single-core / monocœur
	Tipo / Type	SM (ITU-TG.652) / DS (ITU-TG.653) / NZ DS (ITU-TG.655) / ITU-TG.657 A,B / MM (ITU-TG.651)
Cable compatible Compatible cable Cable compatible	Ø (mm)	0,25 / 0,90 / 2,00 / 2,40 / 3,00
Pérdida fusión Splice loss Perte d'épissure	dB	SM 0,02 / MM 0,01 / DS 0,05 / NZDS 0,05 / G.657 0,02
Pantalla Display Écran		4,3" LCD
Repuestos Spare parts Pièces de rechange		batería y electrodos de repuesto incluidos spare battery and electrodes included batterie et electrodes de rechange incluses
Accesorios incluidos Included accessories Accessoires inclus		cortadora de precisión, peladora y maleta de transporte precission cleaver, stripper and carrying case découpage de précision, dénudeur et valise de transport
Temperatura de funcionamiento Operating temperature	°C	-15 ... +60
Tensión de red Mains voltage Tension de secteur	V~	100..240 50/60 Hz
Batería Battery Batterie	V-	11,1 (Li-ion)