941 SENSORS AND ACTUATORS

REMOTE RECEIVER WITH 1 RELAY OUTPUT



Code : **9410335**

Model : **SNI-301**

Description
Wireless receiver with 1 output contact that is connected to room control panel CHC. It receives activation signals from wireless sensors and emergency push-buttons and notifies them to the room control panel to be communicated to ALCAD NURSE CALL system. Control of a single wireless device.

CODE	9410335
MODEL	**SNI-301**
Coding	Up to 32 transmitters can be programmed
Frequency	868,30 MHz
Channels	1
Power supply	12-24 V AC/DC
Power consumption	0.35 W standby at 12 V AC, 1.00 W standby at 24 V AC, 0.23 W standby at 12 V DC, 0.60 W standby at 24 V DC, 0.55 W relay switched at 12 V AC (without load), 1.50 W relay switched at 24 V AC (without load), 0.35 W relay switched at 12 V DC (without load), 1.00 W relay switched at 24 V DC (without load)
Operating modes	ON/OFF (2-button operation) ON/OFF (1-button operation) DEADMAN (maximum 36 seconds)
Outputs	1 potential-free relay contact (changeover)
Maximum contact load	1
Operating temperature	-20 °C to +60 °C
Dimensions	46 x 46 x 25 mm