

# 942 TELEPHONY

## IP PHONE 2LINES POE FOR NURSE STATION



Code : **9420132**

Model : **TFI-401**

### Description

The TFI-401 is the new benchmark for basic IP phones for ACCURO and LIVERO. Equipped with a black and white backlit graphic display, the TFI-401 telephone offers an extraordinary visibility of all the information with the alarms of our systems.

It is an easy-to-use telephone that allows the identification of alerts and their origin, call waiting, call log, call transfers (attended and unattended), volume control, and allows voice communication from call points.

The TFI-401 also has an LED indicator visible from any angle, even at a great distance, intended to notify incoming calls, calls in progress and pending messages. It also has four dynamic keys that can be easily configured to automate telephone functions.

with a single click, in addition to the five fixed function keys that the user can use in an easy and intuitive way. On the other hand, its PoE (Power-over-Ethernet) power system, which guarantees low energy consumption and easy installation.

### Characteristics

- ☐ 2 sip identities
- ☐ 360° degree call/message indicator
- ☐ 4 context sensitive function keys + 5 function keys
- ☐ Graphical Display 132 x 64 pixels with backlight
- ☐ Single position footstand 35 °
- ☐ Wall mountable (1)
- ☐ Hands-free talking (Speakerphone)
- ☐ Digital Signal Processor (DSP) enhanced audio quality
- ☐ 2-port 10/100 Mbps Ethernet switch (RJ45)
- ☐ Power over Ethernet IEEE 802.3af, Class 1
- ☐ SHA-2 based secure PROVISIONING

CODIGO/CODE		9420132
MODELO /MODEL/MODELE		TFI-401
CARACTERISTICAS AUDIO AUDIO FEATURE AUDIO FEATURE	Codecs: <ul style="list-style-type: none"> <li>· G.711 a-law, <math>\mu</math>-law</li> <li>· G.722 (wideband)</li> <li>· G.726, g.729ab, gsm 6.10 (fr)</li> <li>· 10 built-in assignable ringtones</li> <li>· Comfort noise generator (cng)</li> <li>· Voice activity detection (vad)</li> </ul>	
RED Y SEGURIDAD NETWORK & SECURITY RESEAU ET SECURITÉ	<ul style="list-style-type: none"> <li>· Transport Layer Security (TLS)</li> <li>· SRTP (RFC3711), SIPS, SRTCP</li> <li>· VLAN · IEEE 802.1X</li> <li>· LLDP-MED</li> <li>· Web interface password protection</li> <li>· 2 SIP identities/accounts</li> <li>· XML Browser</li> <li>· Call lists for dialed, received, missed calls</li> <li>· Directory with 250 entries</li> <li>· Languages: English, French, Spanish · Additional language support via provisioning</li> <li>· In-band DTMF/out-of-band DTMF/SIP INFO DTMF</li> <li>· Interoperable with all major IP-PBX platforms</li> </ul>	

CODIGO/CODE		9420132
MODELO /MODEL/MODELE		TFI-401
CARACTERISTICAS LLAMADA CALL FEATURES CARACTERISTIQUES DES APPELS	<ul style="list-style-type: none"> <li>· Speed dialing</li> <li>· URL dialing</li> <li>· Local dial plan</li> <li>· Automatic Redial on Busy</li> <li>· Call completion (busy/unreachable) (2) · Caller identification</li> <li>· Call waiting / Call blocking (deny list)</li> <li>· Blocking of anonymous calls (2)</li> <li>· Auto answer</li> <li>· Lists of missed, received and dialed calls · Hold · Music on hold (2)</li> <li>· Handling of up to 2 simultaneous calls</li> <li>· Blind and attended transfer</li> <li>· Call forwarding</li> <li>· 3-way conference on the phone</li> <li>· Call pickup (2)</li> <li>· Call Park, call unpark (2)</li> <li>· Multicast paging</li> </ul>	
CARACTERISTICAS FISICAS HARWARE HARWARE	<ul style="list-style-type: none"> <li>· Dimensions: 205 x 161 x 32 mm (w/o foot stand)</li> <li>· Dimensions: 205 x 161 x 120 mm (with foot stand)</li> <li>· Handset: RJ-4P4C · Headset: RJ-4P4C</li> <li>· Hearing aid compatible (HAC) handset</li> <li>· Power: PoE or 5V DC power adapter (1),</li> <li>· Environmental Conditions:</li> <li>· Ambient temperature: 0° to 35° C (32° to 95° F)</li> <li>· Non-operating temperature: -10 °C to 45 °C</li> <li>· Relative humidity: 5% to 95% noncondensing · Included in delivery:</li> <li>· Base phone unit · Foot stand</li> <li>· Handset with cord</li> <li>· Ethernet cable · Quick Installation Guide</li> <li>· Color: black</li> </ul>	