

942 TELEPHONY 12-LINE IP PHONE, 2.7 []TFT DISPLAY



Code : **9420135**

Model : TFI-404

Description

The new ALCAD TFI-404 offers the best features thanks to its timeless design. This phone is at the forefront, both technically and in appearance. The 2.7 [high resolution color screen is surrounded by eight multi-colored function keys that you can label yourself.

It is a easy-to-use telephone with functionality such as call ID, call waiting, call register, call transfers (attended and unattended) and volume control, which allow its use by the staff as a telephone control station for the reception of calls from the rooms.

Characteristics:

- · 2.7 [high resolution TFT screen
- 32 self-labeling keys (8 physical)
- \cdot User interface that reacts thanks to sensors

 \cdot Hands-free broadband (speaker) Improved sound quality thanks to Digital Signal Processor (DSP)

- · Double Gigabit Ethernet switch port (RJ45)
- \cdot Power over Ethernet IEEE 802.3af, Class 2
- \cdot Compatible with USB headphones (1)
- · Compatible with additional module D7 (1)
- \cdot Compatible with WiFi dongles (1)
- \cdot Compatible with wireless headphones via electronic adapter (EHS) (1)
- \cdot Base with two tilt angles: 46 ° and 28 °

Codigo	9420135
Model	Tfi-404
Call features	Speed dialing
	Url dialing
	Local dial plan
	Automatic redial on busy
	Call completion (busy/unreachable)(2)
	Caller identification
	Call waiting
	Call blocking (deny list)
	Auto answer
	Hold
	Music on hold(2)
	Blind and attended transfer
	Call forwarding
	3-way conferencing on the phone
	Extension monitoring, call pickup(2)
	Call park, call unpark(2)
	Multicast paging
	Dnd mode (do not disturb)
	Keyboard lock
	Client matter code (cmc)(2)
	Unified communications ready
Audio	Codecs:
	G.711 a-law, µ-law
	G.722 (wideband)
	G.726, g.729ab, gsm 6.10 (fr)
	Built-in assignable ringtones
	Comfort noise generator (cng)
	Voice activity detection (vad)
Protocols	Sip (rfc3261)
	Dhcp, ntp
	Http / https / tftp
	Ldap (directory)
	Dual stack ipv4 / ipv6
User interface	Localization (language, time, dial tone)
	Red led for call indication / message waiting
	4 context-sensitive keys
	32 (8 physical)programmable line / function keys with multicolour leds
	Dedicated keys for: message, dnd, directory, menu, transfer, hold, page
	Audio keys with led indication: mute, speakerphone, headset
	Volume key
	5-way navigation key
	Ok and cancel keys

Codigo	9420135
Model	Tfi-404
Security	802.1x authentication and eapol
	Transport layer security (tls)
	Srtp (rfc3711), sips, rtcp
	Https server/client
	Password-protected web interface
	Vpn-support
	Vlan (ieee 802.1q)
	Lldp-med, rtcp-xr
Phone features	Dimensions (approx.):
	205 x 185 x 40 mm (lxwxd) w/o foot stand
	205 x 185 x 200/220 mm (lxwxd) with foot stand
	Weight (approx.): device 450g, footstand 120g
	Input voltage: 5vdc (selv)
	Power supply: poe or 5vdc power adapter(1), 10 watts
	Handset: 4p4c
	Headset: 4p4c; support for snom ehs advanced (1)
	Hearing-aid compatible (hac) handset
	1 x usb 2.0 host port, type a
	Environmental conditions:
	Ambient temperature: 0°c to 35°c (32°f to 95°f)
	storage temperature: -10°c to 45°c (14°f to 113°f)
	Humidity: 5% to 95% (non-condensing)
	Included in delivery:
	Phone unit
	Footstand
	Handset with cord
	Ethernet cable
	Quick start guide