942 TELEPHONY

12-LINE IP PHONE, 2.7 □TFT DISPLAY



Code : **9420135**

Model : **TFI-404**

Description
The new ALCAD TFI-404 offers the best features thanks to its timeless design. This phone is at the forefront, both technically and in appearance. The 2.7 □high resolution color screen is surrounded by eight multi-colored function keys that you can label yourself.
It is a easy-to-use telephone with functionality such as call ID, call waiting, call register, call transfers (attended and unattended) and volume control, which allow its use by the staff as a telephone control station for the reception of calls from the rooms.

Characteristics:
· 2.7 □high resolution TFT screen
32 self-labeling keys (8 physical)
· User interface that reacts thanks to sensors
· Hands-free broadband (speaker) Improved sound quality thanks to Digital Signal Processor (DSP)
· Double Gigabit Ethernet switch port (RJ45)
· Power over Ethernet IEEE 802.3af, Class 2
· Compatible with USB headphones (1)
· Compatible with additional module D7 (1)
· Compatible with WiFi dongles (1)
· Compatible with wireless headphones via electronic adapter (EHS) (1)
· Base with two tilt angles: 46 ° and 28 °

Codigo	9420135
Model	**Tfi-404**
Call features	Speed dialing Url dialing Local dial plan Automatic redial on busy Call completion (busy/unreachable)(2) Caller identification Call waiting Call blocking (deny list) Auto answer Hold Music on hold(2) Blind and attended transfer Call forwarding 3-way conferencing on the phone Extension monitoring, call pickup(2) Call park, call unpark(2) Multicast paging Dnd mode (do not disturb) Keyboard lock Client matter code (cmc)(2) Unified communications ready
Audio	Codecs: G.711 a-law, μ-law G.722 (wideband) G.726, g.729ab, gsm 6.10 (fr) Built-in assignable ringtones Comfort noise generator (cng) Voice activity detection (vad)
Protocols	Sip (rfc3261) Dhcp, ntp Http / https / tftp Ldap (directory) Dual stack ipv4 / ipv6
User interface	Localization (language, time, dial tone)
	Red led for call indication / message waiting 4 context-sensitive keys 32 (8 physical)programmable line / function keys with multicolour leds Dedicated keys for: message, dnd, directory, menu, transfer, hold, page Audio keys with led indication: mute, speakerphone, headset Volume key 5-way navigation key Ok and cancel keys

Codigo	9420135
Model	**Tfi-404**
Security	802.1x authentication and eapol Transport layer security (tls) Srtp (rfc3711), sips, rtcp Https server/client Password-protected web interface Vpn-support Vlan (ieee 802.1q) Lldp-med, rtcp-xr
Phone features	Dimensions (approx.): 205 x 185 x 40 mm (lxwxd) w/o foot stand 205 x 185 x 200/220 mm (lxwxd) with foot stand Weight (approx.): device 450g, footstand 120g Input voltage: 5vdc (selv) Power supply: poe or 5vdc power adapter(1), 10 watts Handset: 4p4c Headset: 4p4c; support for snom ehs advanced (1) Hearing-aid compatible (hac) handset 1 x usb 2.0 host port, type a Environmental conditions:
	Ambient temperature: 0°c to 35°c (32°f to 95°f) storage temperature: -10°c to 45°c (14°f to 113°f) Humidity: 5% to 95% (non-condensing) Included in delivery: Phone unit Footstand Handset with cord Ethernet cable Quick start guide