


# 900

# TERRESTRIAL ANTENNAS

## ANTENNA NEO CHANNELS 21/48 REJ, G = 16DB



Code: 9000200

Model: **NEO-042** 

Antenna for optimal reception of DTT channels, with a high gain (16 dBi). Designed to cover the UHF band up to 694 MHz while rejecting 4G and 5G telephone bands thanks to its built-in rejection filter. Easy to mount and adjust, providing maximum robustness and ensuring complete safety of installation. Stylish design that reflects the excellent electrical and mechanical qualities of the antenna.

### **Applications**

Digital and analogue terrestrial TV installations, collective or individual, where rejection of the LTE700 and LTE800 bands is necessary and high gain and directivity are required. The reflectors prevent interference produced by the signals received from the rear of the antenna.

#### Characteristics

Rejection of LTE700, LTE800 and GSM signals. Manufactured in aluminum, zamak, weather-resistant plastic and galvanised steel. Includes a matching transformer with built in rejection filter, with F-type connector, protected inside a watertight casing (IP55). No tools required for installation. Supplied in an individual pack.



CÓDIGO-CODE-CODE MODELO-MODEL-MODELE			9000200 NEO-042	9000189 NEO-047
Rango de frecuencias Frequency range Gamme de fréquences	MHz		470-694	
Canales Channels Canaux			21-48	
Ganancia Gain Gain	dBi		16	
Rechazo LTE700 LTE700 rejection Rejet LTE700	dB		40	10
Relación delante/detrás Front/back ratio Rapport avant/arriere	dB		30	
Impedancia Impedance Impédance	Ω		75	
Pérdidas de retorno Return loss Pertes de retour	dB		≥ 10	
Polarización Polarity Polarisation			HOR /VER	
Ángulo de apertura Beam width Angle d'ouverture		Н	48	
		V	58	
Longitud Lenght Longueur	mm		800	
Resistencia al viento Wind loading Résistance au vent	N	Н	105	
		V	9	2
Índice de protección Protection index Indice de protection	tection index		IP 53	

