941 SENSORS AND ACTUATORS

NURSE CALL & PRESENCE BUTTON



Code : **9410375**

Model : **LLC-942**

Room touch version peripheral with two buttons: a nurse call button with a red LED and a nurse presence button with a green LED. This peripheral allows patients to call the nurse with the red button. Once initiated the call, the red LED helps to locate the origin of the call easily. The green button is used to either indicate that the nurse is present or to cancel the call. Wall or surface mount.
RJ45 connection.

CÓDIGO-CODE-CODE	9410352, 9410351, 9410353, 9410360, 9410354, 9410355, 9410356, 9410357, 9410358, 9410359	9410370, 9410371, 9410372, 9410373, 9410374, 9410375, 9410376, 9410377, 9410378,
MODELO-MODEL-MODÈLE	LLC-83X, LLC-84X	LLC-93X, LLC-94X
Color de Botón Push button color Boutons couleur	**Verde, Green, Vert:** LLC-X30, LLC-X31, LLC-X32, LLC-X42, LLC-X43 **Azul, Blue, Bleu:** LLC-X32, LLC-X41, LLC-X43, LLC-X47 **Rojo, Red, Rouge:** LLC-X32, LLC-833, LLC-X40, LLC-X42, LLC-X48 **Amarillo, Yellow, Jaune:** LLC-X31, LLC-X32	
Alimentación Power supply Alimentation	24V	
Consumo (stand by) Energy consumption (stand by) Consommation (stand by)	10 mA	
Consumo (max.) Energy consumption (max.) Consommation (max.)	40 mA	
Dimesiones Size Dimensions	80x80x10mm	
Peso Weight Poids	O,08Kg	
Material Material Matériel	ABS/Polycarbonate	
Color Color Couleur	Blanco, White, Blanc (RAL 9001)	
Temperatura operacional Operating temperature Température de fonctionnement	5°C - 55°C	
Indice de protección Protection Indice de Protection	IP 42	
Instalación Mounting Installation	Empotrado, Embedded, Encastré (ACC-100 / ACC-101) En superficie, On surface, En saillie (ACC-110)	
Normativa (seguridad) Normative (security) Norme (sécurité)	EN 60950-1:2006	
Normativa (emisiones electromagneticas) Normative (electromagnetic emissions) Norme (champs magnétique)	EN 61000-3-3	
Conector de red Net Connector Connexion	Bornas, Contact: 8XX	RJ45: LLC-9XX