972 VIDEO DOOR ENTRY SYSTEM KITS

ERLEA PLUS H-FREE 7INCH.KIT.1 BUTTON



Code : **9720165**

Model : **KVS-31221**

Description

2-Wire video door entry system kit for villa. Entrance panel with a touch call button, rainshield, camera with 120° wide view and proximity key reader. This video entry system gives you full control over the access of visitors to your property and, in addition, it allows you to identify the person who calls. The automatic switch-on system makes it possible to see the image captured by the entrance panel camera without having first to receive a call. The automatic switch-on function is useful in situations of surveillance or when you wish to communicate with the entrance panel for whatever reason. As an additional feature, the monitor keeps an automatic visual record of visitors whose calls are unanswered. When a call is not answered, the monitor automatically saves an image of the person making the call. This Kit includes a DIN rail power supply.

CÓDIGO-CODE-CODE	9720165
MODELO-MODEL-MODÈLE	KVS-31221
ALIMENTADOR - POWER SUPPLY UNIT - ALIMENTATION	
ALIMENTACIÓN DE RED *MAINS SUPPLY* ALIMENTATION DE RÉSEAU	100-240 V~ 50/60Hz
	0.3 A (máx.)
SALIDAS *OUTPUTS* SORTIES	15 V⎓
	1 A (máx.)
TEMPERATURA DE FUNCIONAMIENTO *OPERATING TEMPERATURE* TEMPÉRATURE DE TRAVAIL	-10.. +50 °C
MONITOR - MONITOR - MONITEUR	
PANTALLA *SCREEN* ÉCRAN	*7” COLOR TFT LCD* *7” COLOR TFT LCD* *7” COULEUR TFT LCD*
ALIMENTACIÓN *IMPUT POWER* ALIMENTATION	DC15V/1A
TONOS DE LLAMADA *RINGTONE* SONNERIES	*6 Melodías* *6 Ringtones* *6 Sonneries*
INSTALACIÓN *INSTALLATION* INSTALLATION	*De superficie* *Surface mount* *Saillie*
TEMPERATURA DE FUNCIONAMIENTO *OPERATING TEMPERATURE* TEMPÉRATURE DE TRAVAIL	5.. +55 °C
PLACA DE CALLE - ENTRANCE PANEL - PLATINE DE RUE	
CÁMARA *VIDEO UNIT* CAMÉRA	*1/3” Color CCD* *1/3” Color CCD* *1/3” Couleur CCD*
CONEXIÓN *CONNECTION* CONNEXION	*2 Hilos* *2 Wire* *2 fils*
TIEMPO PARA CONTESTAR *TIME TO ANSWER* TEMPS DE RÉPONSE À L’APPEL	90 Seg 90 Sec 90 Sec
TIEMPO DE CONVERSACIÓN TIME FOR CONVERSATION TEMPS DE CONVERSATION	120 Seg 120 Sec 120 Sec
ABREPUERTAS *ELECTRIC LOCK* GÂCHE	15Vdc: ≤500mA
INSTALACIÓN INSTALLATION INSTALLATION	De superficie Surface mount Saillie
PROTECCIÓN IP *IP PROTECTION* PROTECTION IP	IP55
TEMPERATURA DE FUNCIONAMIENTO *OPERATING TEMPERATURE* TEMPÉRATURE DE TRAVAIL	-10.. +50 °C