971 MODULAR ENTRANCE PANELS

AUDIO MODULE 1 BUTTON USOA



Code : **9710014**

Model : **MAG-011**

Description
Complete module for USOA entrance panel. 2 windows. It includes EAG-011 electronic module and CAG-011 front glass

The luminous accessibility icons offer visual information of the operating states of the panel (calling, conversation, door open and system busy), complying with the SUA-9 accessibility regulations of the Technical Building Code and following the recommendations of the ONCE (National organization of the spanish blinds).

9770090 EAG-011 Description
Electronic module for USOA entrance panel. Category: Spare parts.

It includes the audio unit, voice synthesizer (14 languages), a handicap display. This module incorporates 1 tactile call button arranged in a column (right).

9770105 CAG-011 Description
Frontal glass for USOA entrance panel. Category: Spare parts. Front belonging to the complete module MAG-011

USOA is the Alcad entrance panel with a continuous profile and modular composition. It consists of frames of different sizes and with different numbers of windows where the different modules are fitted: as main audio or video module, push-button modules, iaccess module, card holders ... etc. There are two module sizes: P and G. The G modules occupy 2 frame windows, and the P modules occupy a single window.

Its modularity allows total freedom of choice for the creation of compositions and, at the same time, facilitates the integration of all technologies in the same equipment and with the same aesthetics.

Code		9710014	9710015	9710016
Model		**MAG-011**	**MAG-000**	**MAG-021**
Conection		2 Wire		
Number of windows		2		
Front • Materials • Color • Thickness	mm	• Tempered glass • White • 3mm		
Number of tactile buttons		1 Button (Right)	No Button	2 Buttons (Left/Right)
Power supply		DC 12.5-18V		
"Door Opened" Message		14 Selectable languages		
Accessibility Indicator • Complying with regulations		4 Light indicators SUA-9 (CTE)		
Working temperature	°C	-10°C ,,, +55°C		
Packing weight	Kg	0.31	0.30	0.31
Packing dimensions	mm	115 x 105 x 65 mm		