

900 TERRESTRIAL ANTENNAS

NEO ANTENNA, CHAN 21/60, REJ, G = 18DBI



Code : **9000188**

Model : **NEO-088**

Description

Antennas for optimal reception of DTT channels, with the best available gain (18 dBi). Designed to cover the UHF band up to 790 MHz while rejecting the LTE mobile telephone band. Easy to mount and adjust, providing maximum robustness and ensuring complete safety of installation. With a stylish design which perfectly reflects the excellent electrical and mechanical qualities of the antenna.

Applications

Digital and analogue terrestrial TV installations, collective or individual, where rejection of the LTE band is necessary and high gain and directivity are required. The reflectors prevent interference produced by the signals received from the rear of the antenna.

Characteristics

Rejection of LTE and GSM signals. Manufactured in aluminium, zamak, weather-resistant plastic and galvanised steel.. Watertight matching transformer casing (IP55). Matching transformer, with F-type connector and LTE reject filter, protected inside the casing. System of front-fixing reflectors for greater ease of assembly. No tools required for installation. Supplied in an individual pack.

CODE			9000188
MODEL			NEO-088
Frequency range	MHz		470-790
Channel			21-60
Elements			42
Gain	dB _{pV}		18
Front / back ratio	dB		32
Impedance	Ω		75
Retrun loss	dB		>10
Polarity			H / V
Beam width	°H		30
	°V		28
Lenght	mm		1160
Wind loading	N	H	130
		V	100
Connection			F female
Protection index			IP55
Colour			Black/Aluminium
Pack x Code x Unit x Pallet			33 x 1 x1
Packing weight	Kg		3,10
Pallet weight	Kg		117,30
Packing dimensions	mm		800 x 405 x 185
Pallet dimensions	mm		1200 x 800 x 2000