


902

MULTIPLEXERS AND FILTERS

MULTIPLEXER/SPLITTER TV-SAT



Model : MM-214



Multiplexers for masts which combine the signals of terrestrial TV and FM radio with the IF satellite signal from the LNB. The resulting signal is distributed by a single coaxial cable.

Applications


Individual or SMATV installations. The mast multiplexer enables the distribution of the satellite signal to the interior of the building when it is not possible to add a new cable for the satellite.

Characteristics

Shielded zamak chassis, covered by an ABS plastic box for outdoor use. Fixed to the mast by means of a polyamide clamp. F-type connectors. Supplied in individual or multiple packs.

Accessories

9120039 CM-004 Male F connector for Ø6.6mm coaxial. 9080023 MC-302 Male F connector for RG-6 coaxial, Ø7.0 mm





CODE	9020045		
MODEL		MM-214	
Connection		F female	
Inputs		2	
Frequency range	Band	FM/TV	SAT
	MHz	5-862	950-2.400
Insertion loss	dB±TOL	1 ±0,5	
Flatness response	dB	±0.1	±0.3
Channel flatness response	dB	±0.1	
Rejection between inputs	dB	≥35	
Return loss I/O	dB	≥10	
Fixed DC path	mA	-	0-500
	MHz	-	0-3
Pass 22 KHz/DiSEqC		-	Yes
Chroma-luminance delay	ns	<1	-
Operating temperature	°C	-10+65	
Protection index		IP 53	
Units per packaging		1	24
Packing weight	Kg	0.16	4.1
Packing dimensions	mm	11 x 103 x 45	310 x 205 x 250