

903 MAST AMPLIFIERS

POWER SUPPLY 24 VDC 100MA, 4 OUTPUTS



Code: 9030103

Model : **AL-110**

Description

Power supply units for mast amplifiers, 24 voltages. The power supply unit converts the mains supply into DC voltage and injects it into the coaxial cable to feed the amplifier. The signal coming from the antenna is distributed to its outputs. The power supply unit is available with two, four or five outputs. The power supply units are protected against overloads and short circuits. Available on request in 125 or 240

Applications

Individual digital and analogue terrestrial TV installations where mast amplifiers or antenna box preamplifiers are used. The feed voltage should be selected according to the amplifier installed. Characteristics Shielded zamak chassis, covered by an ABS plastic box for outdoor use. Power supply unit insulated from the high frequency circuit, complying with safety standards for both the installer and the user. Fixed to the wall by means of supplied wallplugs and screws. F type connectors. Supplied in individual or multiple packs.

Accessories

9120039 CM-004 Male F connector for Ø6.6 mm coaxial cable 9080023 MC-302 Male F connector for Ø7.0mm coaxial cable. 9120011 RS-275 Type F load of 75 ??. 9040078 DI-007 DIN rail adaptor



CODE			9030	0086	9030103	9030134	
MODEL			AL-100		AL-110	AL-130	
Connection			F female				
Inputs / outputs			1/2		1/4	1/5	
Frequency range	MHz		40-862		5-2,400		
Insertion loss	dB ±TOL	5/40-47 MHz 47-862 MHz 950-2150 MHz 2150-2400 MHz	4.8±0.5 4.8±0.5 -		7.5-7.5 ±1.0 7.5-8.5 ±1.0 8.5-11 ±1.0 11-12.5 ±1.0	8.0-8.5 ±1.0 8.5-9.5 ±1.0 9.5-12 ±1.0 12-13.5 ±1.0	
Output voltage	V		+24				
	mA		0-100				
Peak to peak ripple voltage	mV			-	<150		
Mains voltage	V~		230±10% 50/60 Hz				
	VA		7				
Operating temperature	°C		+5+55				
Protection index			IP 30				
Units per packaging			1	24	1	24	
Packing weight	Kg		0.27	7.10	0.45	11,30	
Packing dimensions	mm		150 x 115 x 50	360 x 315 x 225	125 x 102x 45	312 x 210 x 275	