# MODULAR AMPLIFICATION EQUIPMENT

# POWER SUPPLY 24 VDC 1.7 A (230/240 VAC)



## Code : 9050083

### Model : **AS-125**

#### Description

Compact switching power supply units which permits the installation of up to 18 modules on the support frame.

#### **Applications**

Necessary to supply the amplification modules of the equipment. The number of modules which it can feed varies according to the consumption of the modules and of the consumption of the LNBs in the case of SAT amplifier modules.18 modules can be fed in the case of monochannel amplifiers.

#### Characteristics

Protected against overloads and short-circuits. Made from an aluminium profile and alvanised plate. It includes a protection fuse which the installer can access. Supplied with power cable with faston connector for IEC connector equipment.



CODE		9050000	9050083	
MODEL		AS-102	AS-125	
Output voltage	V	+2	24	
Maximun output current	mA	1100	1700	
Fuse	٧~	250		
	Α	5(Type F)		
Peak to peak ripple voltage	mV	<100	<200	
Mains voltage	٧~	230±15% 50/60 Hz	230±15% 50/60 Hz	240 <sup>+15%</sup> 50/60 Hz
	VA	50	70	
Operating temperature	°C	-10+65		
Protection index		IP 20		
Units per packing		1		
Packing weight	Kg	0.49		
Packing dimensions	mm	190 x 85 x 65		