

# 906 TAP-OFFS AND SPLITTERS

## TAP-OFF IF 4 OUT 24 DB EQUALISED



Code : **9060039**

Model : **FD-419**

### Description

Equalised tap-offs for terrestrial and satellite TV with four tap outputs which cover the 5 to 2,400 MHz frequencies. They distribute part of the input signal to their tap outputs and the main part of the signal continues to the output. The equalisation of the tap outputs compensates the losses of the coaxial cable. Available in different tap-off attenuation values.

### Applications

SMATV installations with a tree-shaped distribution. The tree-shaped distribution reduces the number of distribution elements, and reduces the metres of coaxial cable to be installed, even though the headend to outlet distances remain constant. For installation in buildings with many floors due to the low through loss of the tap-offs.

### Characteristics

Voltage blockage in the tap-offs. Shielded zamak chassis and metal plate. Connectors on the lower part to facilitate the connections. Reduced dimensions. Fits in a 100x100 mm box.

CODE		9060054		9060038		9060039		9060040		
MODEL			FD-410	FD-413		FD-419		FD-425		
Connection			F female							
Outputs			4							
Frequency range		MHz	5 - 2400							
Tap loss										
①		dB ±1.0	5-47 MHz 47-230 MHz 470-862 MHz 950-2150 MHz 2150-2400 MHz	27.0-25.5 25.5-22.5 18.8-15.0 14.5-10.2 10.2-9.7	28.0 28.0-26.0 22.5-18.5 18.0-13.5 13.5		33.0 33.0-31.0 28.0-24.0 23.5-18.5 18.5-17.5		36.0 36.0-34.5 32.5-30.0 30.0-25.5 25.5-25.0	
Flatness response		dB	±1.0							
Through loss										
②		dB ±0.5	5-47 MHz 47-230 MHz 470-862 MHz 950-2150 MHz 2150-2400 MHz	1.5-1.7 1.7-1.8 2.1-2.7 2.9-4.7 4.7-5.0	1.0 1.0-1.3 1.5-2.0 2.0-3.0 3.0-3.5		0.5 0.5-0.8 0.9-1.0 1.2-1.8 1.8-2.0		0.5 0.5-0.6 0.7-0.9 0.9-1.3 1.3-1.5	
Directivity										
④		dB	5-47 MHz 47-862 MHz 950-2150 MHz 2150-2400 MHz	>0 >0-6 >6 >7	>0 >0-6 >6 >6		>0 >0-5 >5-7 >7			
Isolation										
⑤		dB	5-47 MHz 47-862 MHz 950-2150 MHz 2150-2400 MHz	>45 >35 >30 >30	>50 >40 >32 >32		>60 >55 >45 >40		>60 >60 >45 >40	
Return loss										
		dB	5-47 MHz 47-862 MHz 950-2150 MHz 2150-2400 MHz	>15 >15 >13 >13	>15 >16 >16 >16		>17 >18 >17 >15		>18 >18 >17 >16	
Units per packing			6							
Packing weight		Kg	0.45							
Packing dimensions		mm	155 x 95 x 40							