943 ELEMENTOS DE RED

SERVIDOR GAMA MEDIA

Código : **9430104**

Modelo : **SRG-210**

Descripción
El servidor SRG-210 centraliza toda la gestión de servicios del sistema IPTV a través de un servidor de alta capacidad.
El servidor tiene una gran capacidad de configuración para la gestión del sistema IPTV y facilidad de conexión con software de terceros.
El SRG-210 ofrece la versatilidad y flexibilidad para alimentar una variedad de aplicaciones. Con un conjunto equilibrado de recursos, capacidad de expansión y asequibilidad, el SRG-210 se adapta a las demandas del centro de datos moderno con el diseño optimizado de valor ideal. Optimice automáticamente el rendimiento con el ajuste de la aplicación con un solo botón y escale para demandas futuras con hasta 14 unidades de 3,5".
- Escale los recursos informáticos con los procesadores escalables Intel® xeon® de segunda generación y adapte el rendimiento en función de sus requisitos de carga de trabajo únicos.
- Optimice automáticamente el rendimiento de la aplicación con el ajuste de un solo botón.
- almacenamiento flexible con hasta 14 unidades de 3,5.
- Libere almacenamiento con SSD m.2 optimizado para arranque.
- Gestión de 1 a 299 STB sin VoD o de 1 a 99 STB con VoD.

CODE	9430104
MODEL	SRG-210
PROCESSOR	Up to one Intel® Xeon® E-2200 product family processor with up to 8 cores per processor Up to one Intel® Pentium® G5420 processor up to 2 cores per processor Up to one Intel® Core i3® 9100 processor up to 4 cores per processor Up to one Intel® Celeron® G4930 processor up to 2 cores per processor
MEMORY	DIMM Speed Up to 2666 MT/s Memory Type UDIMM Memory Module Slots 4 UDIMM slots Maximum RAM UDIMM 64GB
STORAGE CONTROLLERS	Internal Controllers PERC H330, H730p, HBA330 External Controllers 12Gbps SAS HBA Software RAID S140 Boot Optimized Storage Subsystem (BOSS): - 2 x M.2 240GB (RAID 1 or No RAID) - 1 x M.2 240GB (No RAID only) Internal Dual SD Module (IDSDM)*: - 2x microSD (16GB, 32GB or 64GB) - 1x microSD (16GB, 32GB or 64GB)
DIMENSIONS & WEIGHT	Width 434.0mm (17.1") Depth 595.6mm (23.5") Weight 13.6kg (29.9lbs.)
SECURITY	Security Cryptographically signed firmware Secure Boot Secure Erase Silicon Root of Trust System Lockdown (requires OpenManage Enterprise) TPM 1.2/2.0, TCM 2.0 optional
I/O & PORTS	Network Options 2 x 1GbE LOM Front Ports 1 x Dedicated iDRAC direct micro-USB 1 x USB 2.0 Rear Ports 1 x Serial 2 x USB 3.0 1 x VGA Internal Ports 1 x USB 3.0 PCie 2 x PCIe Gen3 slots