

941

SENSORES Y ACTUADORES

PULSADOR PARED PRES. 1ª Y 2ª, Y LLAMADA

Código : **9410353**

Modelo : **LLC-832**

Base de pared con 4 pulsadores (llamada, presencia, código azul y presencia 2ª).



| CÓDIGO-CODE-CODE | 9410352, 9410351, 9410353, 9410360, 9410354, 9410355, 9410356, 9410357, 9410358, 9410359 | | 9410370, 9410371, 9410372, 9410373, 9410374, 9410375, 9410376, 9410377, 9410378, | |
|---|---|---------------|--|--|
| MODELO-MODEL-MODÈLE | LLC-83X, LLC-84X | | LLC-93X, LLC-94X | |
| Color de Botón Push button color Boutons couleur | Verde, Green, Vert: LLC-X30, LLC-X31, LLC-X32, LLC-X42, LLC-X43 Azul, Blue, Bleu: LLC-X32, LLC-X41, LLC-X43, LLC-X47 Rojo, Red, Rouge: LLC-X32, LLC-833, LLC-X40, LLC-X42, LLC-X48 Amarillo, Yellow, Jaune: LLC-X31, LLC-X32 | | | |
| Alimentación Power supply Alimentation | 24V | | | |
| Consumo (stand by) Energy consumption (stand by) Consommation (stand by) | 10 mA | | | |
| Consumo (max.) Energy consumption (max.) Consommation (max.) | 40 mA | | | |
| Dimesiones Size Dimensions | 80x80x10mm | | | |
| Peso Weight Poids | 0,08Kg | | | |
| Material Material Matériel | ABS/Polycarbonate | | | |
| Color Color Couleur | Blanco, White, Blanc (RAL 9001) | | | |
| Temperatura operacional Operating temperature Température de fonctionnement | 5°C - 55°C | | | |
| Indice de protección Protection Indice de Protection | IP 42 | | | |
| Instalación Mounting Installation | Empotrado, Embedded, Encastré (ACC-100 / ACC-101) En superficie, On surface, En saillie (ACC-110) | | | |
| Normativa (seguridad) Normative (security) Norme (sécurité) | EN 60950-1:2006 | | | |
| Normativa (emisiones electromagneticas) Normative (electromagnetic emissions) Norme (champs magnétique) | EN 61000-3-3 | | | |
| Conector de red Net Connector Connexion | Bornas, Contact: 8XX | RJ45: LLC-9XX | | |