942 TELEFONIA

TELEFONO IP 20 LINEAS PANTALLA TACTIL 7"



Código : **9420148**

Modelo : **TFI-701**

Descripción
Con una pantalla táctil de 7 ", el TFI-701 es la estación de enfermería ideal para responder a las llamadas de los pacientes, acceder al visor ACCURO, ver la información del paciente y administrar todas las tareas.

Caracteristicas:
- Sistema operativo Android 9.0
- 20 líneas SIP
- Pantalla táctil a color de 7 pulgadas con 112 teclas DSS
- Cámara USB externa (opcional)
- Videollamada HD 720P, códec de vídeo H.264
- Audio HD con altavoz, códec de banda ancha G.722 y códec de audio Opus
- WiFi y Bluetooth integrados de 2,4G / 5G
- Soporte de auriculares EHS
- Soporte de punto de acceso SIP
- Agenda telefónica local hasta 2000 entradas
- Admite PoE y fuente de alimentación externa

CODE	9420148
MODEL	**TFI-701**
GENERIC	20 SIP lines, HD voice, 20 SIP Lines, HD Voice, Support receiving videocall, PoE Enabled, 7-inch(1024x600) color touch screen, Handset/Hands-free/Head set mode, Intelligent DSS Keys (Virtual buttons), Optional External Power Supply.
OPERATION SYSTEM	Android 9.0
PHONE FEATURES	Local Phonebook (2000 entries) Remote Phone book (XML/LDAP ,2000entries) Intelligent Search for Contacts and Call Log Call logs(In/out/missed,1000entries) Black/White List Call Filter, Screensaver Voice Message Waiting Indication(VMWI) Programmable DSS/Softkeys Built-in Wi-Fi 2.4GHz, 802.11b/g/n 5GHz, 802.11a/n/ac
VIDEO	Video decoding: H.264 Video call resolution: CIF/VGA/4CIF/720P/1080P Image format: JPEG/PNG/BMP Video format: MP4 Bandwidth selection: 64kbps~4Mbps Framerate selection: 5~30fps Video from remote site can be displayed in full screen 3-way Video Call with External Camera
AUDIO	HD Voice Microphone/Speaker (Handset/Hands-free,0~7KHz Frequency Response) HAC handset Wide band ADC/DAC16KHzSampling Narrow band Codec:G.711a/u,G.729AB,iLBC Wide band Codec:G.722,Opus Noise Reduction(NR)
NETWORK	Physical: 10/100/1000Mbps Ethernet, dual bridged port for PC bypass,IPMode:IPv4,IP Configuration: Static/DHCP,Network Access Control: 802.1x, VLAN, QoS
PHYSICAL SPECIFICATIONS	Color: Black LCDx1:7inch(1024x600) color touch screen Keypad: 26keys HD Handset (RJ9)x1 Standard RJ9 Handset Wirex1 1.5M CAT5 Ethernet Cablex1 Back Rack x 1 RJ9 Port x2: Handsetx1, Headsetx1 RJ45 Portx2: Network x1, PC x1 (Bridged to Network) USB2.0 Portx1: Standard A, Connect with Flash Driver Safety key holex1 Power: 5V/2A or PoE Power Consumption (PoE):1.596~11.86W Power Consumption (Adapter):0.907~9.38W Working Temperature:0~45°C Working Humidity:10~95% Installation: Desktop Stand Device Dimensions: · Desktop Stand(Angles1): 268x185x189mm · Desktop Stand(Angles2): 268x201x168mm · Gift Box Dimensions:304x297x66mm