943 ELEMENTOS DE RED

CAMARA AI DOMO POE IP66

Código : **9430123**

Modelo : **CMA-100**

Descripción:
La solución de reconocimiento facial de ALCAD para la localización de personas en tiempo real ofrece una alta precisión gracias a su tecnología avanzada de inteligencia artificial, comparación de rostros, búsqueda inteligente, búsqueda de imágenes de rostros y administración de bases de datos de rostros.
Con ello, no solo obtiene un sistema de localización en tiempo real, sino que se obtiene un sistema de errantes no intrusivo que evite la fuga de pacientes de las instalaciones.

CÓDIGO-CODE-CODE	9430123
MODELO-MODEL-MODÈLE	CMA-100
Video Compression	H.265/H.264
Resolution	2MP 1920(H)×1080(V)
Image Sensor	1/2.7" Progressive CMOS
Min. Illumination	Color 0.02lux @ F1.2(AGC ON)
Shutter	1/5 ~ 1/20000s
Slow shutter	Support
Lens	2.7 ~ 13.5 mm
F No.	F1.6±5%
Day & Night	IR cut filter with auto switch
WDR	Digital WDR
Video bit rate	128Kbps ~ 8Mbps
Dual Stream	Main, Moblie
Frame Rate	Mainstream(1-30fps optional) 1080P(1920x1080), 960P(1280x960), 720P(1280x720) Substeam VGA(640x480), QVGA (320x240)
Image Settings:	Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Support
Privacy Mask	Support
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE,
	SMTP,NTP,UPnP,SNMP,HTTPS,FTP,
System Compatibility	ONVIF(Profile S, Profile G)
Interface	RJ45 10M / 100M Ethernet interface x1
Led &IR Range	40 pcs Up to 40m
Video Output:	no
Water Proof	IP 66
Power Supply	DC 12V/POE
Consumption	≤6W
Storage Temperature	-30~+60°C
Operating Temperature	-30~+55°C