916 DISTRIBUCION FIBRA OPTICA

KIT TRANSMISOR OPTICO SAT-TV 7DBM Y LNB

Código : **9160108**

Modelo : **OT-622**

Kit óptico compuesto de: LNB Wholeband, capaz de recibir y transmitir la totalidad de un satélite mediante 2 cables coaxiales (V y H), transmisor óptico de 1310nm, con entradas SAT (V y H) y terrestre y salida óptica FC/UPC, y fuente de alimentación externa para alimentar tanto el transmisor óptico como la LNB.
Este kit nos permite emitir señales satélite y terrestre mediante un solo cable de fibra óptica a un máximo de 32 usuarios.

CODIGO-CODE-CODE		9160108
MODELO-MODEL-MODÈLE		OT-622
OPTICAL		
Optical output		FC/UPC
Optical wavelength	nm	1310
Opticual output power	dBm	+7
Return loss	dB	20
RF SIGNAL SATELLITE		
RF Input		F
Input frequency Wideband	MHz	290.. 2340
Nominal impedance	Ω	75
Input power*	dBµV	70.. 85
RF SIGNAL TERRESTRIAL		
RF Input		F
Input frequency	MHz	88.. 694
Nominal impedance	Ω	75
Input power	dBµV	70
GENERAL		
Power supply		F
Input voltage	Vdc	20
Current consumption	mA	350
Output voltage SAT (V) & TERR	Vdc	12
Ouput voltage SAT (H)	Vdc	8
Max upstream current	mA	500
Dimensions	mm	165x169x105
Operating temperature	°C	-20.. +60

*For 40 transponders