912 MATERIEL POUR TV-SAT ET MODULATEURS

MULTIPLEXEUR ACTIF 6 ENTREES

Code : **9120212**

Modèle : **AMU-600**

Description
Multiplexeur actif avec 6 entrées dans la bande terrestre. Grâce à ces 6 entrées, l'équipement mélange un nombre élevé de canaux dans la bande terrestre. L'amplification de 7 dB compense les pertes lors du multiplexage.

Applications
Installations de télévision terrestre collective analogique ou numérique de taille moyenne. L'appareil est installé en tête de réseau dans l'étape précédant l'installation des amplificateurs à large bande. Cela permet d'obtenir une sortie égalisée sans perte de qualité. Compatible avec toutes les installations TV collectives du groupe terrestre. Est ajusté en utilisant un contrôleur de gain.

Caractéristiques
Régulation du niveau de sortie pour atteindre le niveau requis par l'amplificateur de tête de l'installation. Châssis zamak blindé avec caches latéraux en métal. Connecteurs de type F

CODE		9120212	
MODEL		AMU-600	
Number of inputs		6	
Connection		F female	
Frecuency range	MHz	47-862	
Number of outputs		1+ test(-20dB)	
Gain	dB	7	
Input level	dBµV	65.. 75	
Output test point	dB±TOL	-30 ±1.0	
Output level	dBµV	87 (CTB -60 dB) 87 (CSO -60 dB)	
Adjustable gain range	dB	15	
Power supply	V⎓	24	12
	mA	120	105
Operating temperature	ºC	-10..+65	
Room temperature with/ without fan	ºC	-10..+55/+45	
Protection index		IP 30	
Units per packing		1	
Packing weight	Kg	1.4	
Packing dimensions	mm	270 x 170 x 38	