941 CAPTEURS

WC TIRETTE IP65

Code : **9410104**

Modèle : **LLC-122**

Description
Périphérique de salle de bain avec cordon d'appel de 1,8 m, cordon d'arrêt et une LED rouge pour l'installation dans des environnements humides (douches, saunas, etc.) Il permet au patient de lancer un appel via la tirette ou par le bouton d'appel rouge. Une fois lancé l'appel du patient, le voyant rouge permet de faciliter l'identification de l'état de l'appel. Il dispose d'un mécanisme d'anti-strangulation qui permet de diviser le cordon de la tirette en 2 parties, et ainsi d'éviter les accidents. Il dispose d'une boule rouge à l'extrémité qui permet au patient une meilleure localisation de la tirette. Montage encastré avec boîte universelle.

Specifications	
Call pull-cord	Switch type: reed contact
	Length: 1,8 m PVC antibacterial color red (RAL 3005 , wine red)
	Anti-strangulation mechanism 6Kg
	Pull cord pull (RAL 3005, red wine)
Power supply	24 VDC
Consumption (standby)	0 mA
Consumption (switch activation)	125 mA
Dimensions (width x height x depth)	80 x 80 x 20 mm
Weight	130g
Material	ABS / Polycarbonate
Color (trim)	White (RAL 9010, pure white)
Operating temperature	-5°C…55°C
Protection degree	IP 66
Cleaning	Resistant to cleaning agents according to EN 13727
Mounting	Mounted (standard box, installation depth 38mm ACC-100 / ACC-101)
Approvals	CE