943 COMMUTATEUR GERE LAYER 2 - 24P 1GBPS

Code : **9430026**

Modèle : **SWI-143**

Description
Commutateur à 24 ports pour le raccordement des équipements de réseau IP dont le système ATICA MONITORING est composé, tels que les postes de chambre (CHC-040), les téléphones IP, l'unité de contrôle centrale ou la station de base de téléphonie DECT (DEC-301). Des 24 ports, 2 sont des ports à double personnalité. Ceux-ci sont prévus pour le raccordement des modules à fibres optiques afin de prolonger le réseau dans les installations où les distances à couvrir sont plus importantes que 90m ou aux endroits où il est impossible d'installer le câble UTP.

ALCAD

I/O EXTERNAL PORTS
24 ports 10/100/1000 10 base-T type IEEE 802.3, 100 base-Tx type IEEE 802.3u, 1000 base-T Gigabit Ethernet type IEEE 802.3ab
2 dual personality ports: each port can be used as an RJ-45 10/100/1000Mbps or with a slot for mini- GBIC to be used with mini-GBIC transceivers

SPECIFICATIONS	
Latency	100Mb < 20 µs. For 64 bytes architecture in store-and-forward mode
Size of the address table	8000 inputs
Routing / switching capacity	48Gbps.
Active flow control	Half-duplex back-pressure control. Full-duplex IEEE 802.3x pause frame flow control
Priority	IEEE 802.1p
Rack mounting	In 19" telco Rack EIA standard
Power supply	100-240VAC/50-60Hz universal connection
Power consumption	Maximum 29W
Security	UL (UL 1950)/cUL listed. IEC950/EN60950. CE marked cUL 60950 (listado)/EN60950 (low voltage directive)
Dimensions	440 x 205 x 43mm
Weight	2,7kg.
Operating temperature	0ºC to 40ºC
Storing temperature	–40ºC to 70ºC
Approval	CEM CE marked FCC Part 15 Clase A VCCI Clase A EN 55022 (CISPR 22) EN 55024 (CISPR 24) C-Tick. FCC Rules Part15, Subpart B Clase A EN 55022