941

# CAPTEURS

## TELERECEPTEUR AVEC 1 SORTIE DU RELAIS

Code : **9410335**

Modèle : **SNI-301**

Description
Récepteur sans fil avec 1 sortie de relais qui se connecte à la centrale de chambre CHC. Il reçoit le signal d'activation des capteurs ou boutons sans fil associés et le notifie à la pièce centrale à laquelle il est connecté en émulant la pression d'un bouton pour la communication de l'activation des périphériques sans fil au système ALCAD NURSE CALL. Contrôle d'un seul appareil sans fil.

| CODE | 9410335 |
|---|---|
| **MODEL** | **SNI-301** |
| Coding | Up to 32 transmitters can be programmed |
| Frequency | 868,30 MHz |
| Channels | 1 |
| Power supply | 12-24 V AC/DC |
| Power consumption | 0.35 W standby at 12 V AC,<br>1.00 W standby at 24 V AC,<br>0.23 W standby at 12 V DC,<br>0.60 W standby at 24 V DC,<br>0.55 W relay switched at 12 V AC (without load),<br>1.50 W relay switched at 24 V AC (without load),<br>0.35 W relay switched at 12 V DC (without load),<br>1.00 W relay switched at 24 V DC (without load) |
| Operating modes | ON/OFF (2-button operation)<br>ON/OFF (1-button operation)<br>DEADMAN (maximum 36 seconds) |
| Outputs | 1 potential-free relay contact (changeover) |
| Maximum contact load | 1 |
| Operating temperature | -20 °C to +60 °C |
| Dimensions | 46 x 46 x 25 mm |