

942 TERMINAUX

TELEPHONE SIP 7" SCREEN ANDROID



Code: 9420131

Modèle : TFI-361

Description

TFI-361 is an Android-based multimedia terminal with a 7 inch touch screen and a 1.3M CMOS sensor camera. It supports H.264/H.263 codecs with adaptive bandwidth adjustment. The 7 \Box touch screen offers excellent user experiences such as high quality videophone, smooth internet surfing, various

Android Apps and daily information.

☐ AutoP: FTP/TFTP/HTTP/HTTPS

Characteristics

Characteristics
☐7 inch capacitive touch screen TFT LCD, 1024*600 pixels
□ 1.3M pixels CMOS camera with privacy shutter
Dual switched 10/100/1000Mbps Ethernet ports, supporting IEEE802.11af
and IEEE802.az Energy Efficient Ethernet
□ Built-in Bluetooth, USB and Wi-Fi feature
☐ Built-in Radio Frequency Module: support either 868MHz or 433MHz
Android 5.1 Operating System and support Android API for the 3rd party
Android application installation
□ Voice and Video Codec : PCMA,PCMU, G.722, G.723, G.729, H.263,
H.264

☐ Protocol: SIP RFC3261, TCP/UDP/IP, PPPoE, RTP/RTCP, HTTP/HTTPS, etc



CODE	9420131
MODEL	TFI-361
Video Features	 Video Codec: H.263,H.264 Video Solution: QCIF, CIF, VGA, 4CIF, 720P Video Bitrate: 64kbps-2Mbps Adaptive Bandwidth Adjustment Video Character: PIP, Full Screen, Local Video ON/OFF Control Image Codec: JPEG, GIF, PNG, BMP
Audio Features	 Wideband Audio Codec: G.722 Narrowband Audio Codec: PCMA,PCMU, G.723, G.729 VAD CNG Echo Canceller G.165/G.168 Full-Duplex Speakerphone 4 DTMF modes: RFC2833,In-Band, SIP INFO, Auto
Network and Security	 SIP V2(RFC3261) UDP/TCP/IP RTP/RTCP ARP/RARP NAT Traversal: Static NAT configure, SIP Keep Alive IP Assignment: Static IP, DHCP, PPPoE NTP For Auto Time Setting Network Packet Capture TFTP/FTP/HTTP/HTTPS Client API QoS: Layer 2 (802.1Q, 802.1p) and Layer 3 (ToS, DiffServ) HTTPS MD5 and MD5-sess Based Authentication Access for Administration



CODE	9420131
MODEL	TFI-361
Phone Features	 Android 5.1 Operation System Support 6 SIP accounts Call Waiting Call Transfer Call Hold Mute Redial Speed Dial Direct IP call 6-Way Conference DND (Do Not Disturb) Volume Adjustable Ring Tones Selectable Multi-Languages Support Default Apps: Phonebook, Weather, Google Play, Digital Photo Frame, Stock, News Feeds, Calendar, World Clock, Alarm Clock, Email, Camera, File Browser, Games. 3rd Party Android Applications
Directory	 Local Phonebook up to 3000 Groups Phonebook with Contact Picture Favorites Blacklist Call Logs: 600 Entries (200 Missed Calls; 200 Dialed Calls; 200 Received Calls.) LDAP Intelligent Search Method
Management	 Firmware Local Update: USB Flash Disk Firmware Remote Update: FTP method Auto Provisioning Using FTP/TFTP/HTTPS System Log Export Restore To Factory Default Configuration Managements Via LCD
Physical Features	 7 Inch Capacitive Touch Screen, Resolution 1024*600, 16:9 Wide Screen Aspect Ratio 3 LED Lights (1 Power Light, 1 Network Light, and 1 Message Light) 28 Keys RK3288 Chipset Flash Memory 8GB 2GB DDR3 Memory Foot Stand 1.3 Mega Pixels CMOS Camera, Free Rotation RJ9 Handset 3.5mm Headset jack 2 RJ45 10/100/1000M Ethernet Jacks Energy Efficient Ethernet: IEEE802.3az Power over Ethernet: IEEE802.3af 868MHz or 433MHz RF Module Bluetooth Wireless Access: 802.11b/g/n 1 USB 2.0 1 HDMI Video Out Port Power Adapter: AC 100~240V Input, DC 12V/1A Output Dimensions: 240*192*106mm Operating Temperature: 32° ~ 104°F (0~ 40°C)