# 942 TERMINAUX

## TÉLÉPHONE IP 12 LIGNES, ÉCRAN TFT 2,7 PO




Code : **9420135**

Modèle : **TFI-404**

Description
The new ALCAD TFI-404 offers the best features thanks to its timeless design. This phone is at the forefront, both technically and in appearance. The 2.7 high resolution color screen is surrounded by eight multi-colored function keys that you can label yourself.
It is a easy-to-use telephone with functionality such as call ID, call waiting, call register, call transfers (attended and unattended) and volume control, which allow its use by the staff as a telephone control station for the reception of calls from the rooms.

Characteristics:
· 2.7 high resolution TFT screen
32 self-labeling keys (8 physical)
· User interface that reacts thanks to sensors
· Hands-free broadband (speaker) Improved sound quality thanks to Digital Signal Processor (DSP)
· Double Gigabit Ethernet switch port (RJ45)
· Power over Ethernet IEEE 802.3af, Class 2
· Compatible with USB headphones (1)
· Compatible with additional module D7 (1)
· Compatible with WiFi dongles (1)
· Compatible with wireless headphones via electronic adapter (EHS) (1)
· Base with two tilt angles: 46 ° and 28 °

| Codigo | 9420135 |
|---|---|
| **Model** | **Tfi-404** |
| Call features | Speed dialing<br>Url dialing<br>Local dial plan<br>Automatic redial on busy<br>Call completion (busy/unreachable)(2)<br>Caller identification<br>Call waiting<br>Call blocking (deny list)<br>Auto answer<br>Hold<br>Music on hold(2)<br>Blind and attended transfer<br>Call forwarding<br>3-way conferencing on the phone<br>Extension monitoring, call pickup(2)<br>Call park, call unpark(2)<br>Multicast paging<br>Dnd mode (do not disturb)<br>Keyboard lock<br>Client matter code (cmc)(2)<br>Unified communications ready |
| Audio | Codecs:<br>G.711 a-law, μ-law<br>G.722 (wideband)<br>G.726, g.729ab, gsm 6.10 (fr)<br>Built-in assignable ringtones<br>Comfort noise generator (cng)<br>Voice activity detection (vad) |
| Protocols | Sip (rfc3261)<br>Dhcp, ntp<br>Http / https / tftp<br>Ldap (directory)<br>Dual stack ipv4 / ipv6 |
| User interface | Localization (language, time, dial tone) |
| | Red led for call indication / message waiting<br>4 context-sensitive keys<br>32 (8 physical )programmable line / function keys with multicolour leds<br>Dedicated keys for: message, dnd, directory, menu, transfer, hold, page<br>Audio keys with led indication: mute, speakerphone, headset<br>Volume key<br>5-way navigation key<br>Ok and cancel keys |

| Codigo | 9420135 |
|---|---|
| **Model** | **Tfi-404** |
| Security | 802.1x authentication and eapol<br>Transport layer security (tls)<br>Srtp (rfc3711), sips, rtcp<br>Https server/client<br>Password-protected web interface<br>Vpn-support<br>Vlan (ieee 802.1q)<br>Lldp-med, rtcp-xr |
| Phone features | Dimensions (approx.):<br>205 x 185 x 40 mm (lxwxd) w/o foot stand<br>205 x 185 x 200/220 mm (lxwxd) with foot stand<br>Weight (approx.): device 450g, footstand 120g<br>Input voltage: 5vdc (selv)<br>Power supply: poe or 5vdc power adapter(1), 10 watts<br>Handset: 4p4c<br><br>Headset: 4p4c; support for snom ehs advanced (1)<br>Hearing-aid compatible (hac) handset<br>1 x usb 2.0 host port, type a<br>Environmental conditions: |
| | Ambient temperature: 0°c to 35°c (32°f to 95°f)<br>storage temperature: -10°c to 45°c (14°f to 113°f)<br>Humidity: 5% to 95% (non-condensing)<br>Included in delivery:<br>Phone unit<br>Footstand<br>Handset with cord<br>Ethernet cable<br>Quick start guide |