942 TERMINAUX

TÉLÉPHONE IP 4 LIGNES, RÉTRO-ÉCLAIRÉ TFT



Code : **9420133**

Modèle : **TFI-402**

The TFI-402 is a state-of-the-art, full-featured IP desk phones for small or large scale deployments suitable for use in a multitude of business scenarios. Supporting four SIP identities and five programmable keys with built in LEDS for visual call indication alerts, the TFI-402 blends an elegant utilitarian design for high usability with high performance and affordability. It is a easy-to-use telephone with functionality such as call ID, call waiting, call register, call transfers (attended and unattended) and volume control, which allow its use by the staff as a telephone control station for the reception of calls from the rooms.

CODE	9420133
MODEL	TFI-402
AUDIO FEATURE	Codecs: · G.711 a-law, μ-law · G.722 (wideband) · G.726, g.729ab, gsm 6.10 (fr) · 10 built-in assignable ringtones · Comfort noise generator (cng) · Voice activity detection (vad)
NETWORK & SECURITY	· 802.1X Authentication and EAPOL · Transport layer security (TLS) · SRTP (RFC3711), SIPS, RTCP · HTTPS server/client · Password-protected web interface · VPN support · VLAN (IEEE 802.1Q) · LLDP-MED, RTCP-XR
CALL FEATURES	· Speed dialing · URL dialing · Local dial plan · Automatic redial on busy · Call completion (busy/unreachable) · Caller identification · Call waiting · Call blocking (deny list) · Auto answer · Hold · Music on hold(2) · Handling of up to 4 simultaneous calls · Blind and attended transfer · Call forwarding · 3-way conferencing on the phone · Extension monitoring, call pickup(2) · Call park, call unpark(2) · Multicast paging · DND mode (do not disturb) · Keyboard lock · Client matter code (CMC)(2) · Unified communications ready

CODE	9420133
MODEL	TFI-402
PHISICAL FEATURES	· Dimensions (approx.): · 205 x 185 x 40 mm (LxWxD) w/o footstand · 205 x 185 x 200/220 mm (LxWxD) with footstand · Weight (approx.): device 440 g, footstand 120 g · Input voltage: 5 Vdc (SELV) · Power supply: PoE or 5Vdc power adapter (1) · Handset: 4P4C connector · Headset: 4P4C · Hearing aid compatible (HAC) handset · Environmental conditions: · Ambient temperature: 0°C to 35°C (32°F to 95°F) · Storage temperature: -10°C to 45°C (14°F to 113°F) · Humidity: 5% to 95% (non-condensing) · Included in delivery: · Phone unit · Footstand · Handset with cord · Ethernet cable · Quick Installation Guide · Color: black · Warranty: 2 Years