941 CAPTEURS

INTERRUPTEUR MURELE CODE BLEU

Code : **9410374**

Modèle : **LLC-941**

Room device with blue coded call button with blue LED indicator. Allows you to launch a call from the blue call button. Once the call has started, the blue LED indicator allows easy identification of the place from which the call has been launched.

CÓDIGO-CODE-CODE	9410352, 9410351, 9410353, 9410360, 9410354, 9410355, 9410356, 9410357, 9410358, 9410359	9410370, 9410371, 9410372, 9410373, 9410374, 9410375, 9410376, 9410377, 9410378,
MODELO-MODEL-MODÈLE	LLC-83X, LLC-84X	LLC-93X, LLC-94X
Color de Botón Push button color Boutons couleur	**Verde, Green, Vert:** LLC-X30, LLC-X31, LLC-X32, LLC-X42, LLC-X43 **Azul, Blue, Bleu:** LLC-X32, LLC-X41, LLC-X43, LLC-X47 **Rojo, Red, Rouge:** LLC-X32, LLC-833, LLC-X40, LLC-X42, LLC-X48 **Amarillo, Yellow, Jaune:** LLC-X31, LLC-X32	
Alimentación Power supply Alimentation	24V	
Consumo (stand by) Energy consumption (stand by) Consommation (stand by)	10 mA	
Consumo (max.) Energy consumption (max.) Consommation (max.)	40 mA	
Dimesiones Size Dimensions	80x80x10mm	
Peso Weight Poids	O,08Kg	
Material Material Matériel	ABS/Polycarbonate	
Color Color Couleur	Blanco, White, Blanc (RAL 9001)	
Temperatura operacional Operating temperature Température de fonctionnement	5°C - 55°C	
Indice de protección Protection Indice de Protection	IP 42	
Instalación Mounting Installation	Empotrado, Embedded, Encastré (ACC-100 / ACC-101) En superficie, On surface, En saillie (ACC-110)	
Normativa (seguridad) Normative (security) Norme (sécurité)	EN 60950-1:2006	
Normativa (emisiones electromagneticas) Normative (electromagnetic emissions) Norme (champs magnétique)	EN 61000-3-3	
Conector de red Net Connector Connexion	Bornas, Contact: 8XX	RJ45: LLC-9XX