

941

CAPTEURS

INTERRUPEUR D'APPEL D'INFIRMIERE BUS

Code : **9410373**

Modèle : **LLC-940**

CÓDIGO-CODE-CODE	9410352, 9410351, 9410353, 9410360, 9410354, 9410355, 9410356, 9410357, 9410358, 9410359	9410370, 9410371, 9410372, 9410373, 9410374, 9410375, 9410376, 9410377, 9410378,
MODELO-MODEL-MODELE	LLC-83X, LLC-84X	LLC-93X, LLC-94X
Color de Botón Push button color Boutons couleur	Verde, Green, Vert: LLC-X30, LLC-X31, LLC-X32, LLC-X42, LLC-X43 Azul, Blue, Bleu: LLC-X32, LLC-X41, LLC-X43, LLC-X47 Rojo, Red, Rouge: LLC-X32, LLC-833, LLC-X40, LLC-X42, LLC-X48 Amarillo, Yellow, Jaune: LLC-X31, LLC-X32	
Alimentación Power supply Alimentation		24V
Consumo (stand by) Energy consumption (stand by) Consommation (stand by)		10 mA
Consumo (max.) Energy consumption (max.) Consommation (max.)		40 mA
Dimesiones Size Dimensions		80x80x10mm
Peso Weight Poids		0,08Kg
Material Material Matériel		ABS/Polycarbonate
Color Color Couleur		Blanco, White, Blanc (RAL 9001)
Temperatura operacional Operating temperature Température de fonctionnement		5°C - 55°C
Indice de protección Protection Indice de Protection		IP 42
Instalación Mounting Installation		Empotrado, Embedded, Encastré (ACC-100 / ACC-101) En superficie, On surface, En saillie (ACC-110)
Normativa (seguridad) Normative (security) Norme (sécurité)		EN 60950-1:2006
Normativa (emisiones electromagnéticas) Normative (electromagnetic emissions) Norme (champs magnétique)		EN 61000-3-3
Conector de red Net Connector Connexion	Bornas, Contact: 8XX	RJ45: LLC-9XX